

# Modèles de genou pour la marche bipède

Arnaud Hamon, Yannick Aoustin  
IRCCyN, Nantes

Le 4 juin 2010

Introduction

The Human knee joint

Solutions for the knee joint

Optimization and results

Conclusion

**Introduction**

**The Human knee joint**

**Solutions for the knee joint**

**Optimization and results**

**Conclusion**

Introduction

Introduction

The Human knee joint

Solutions for the knee joint

Optimization and results

Conclusion

# Introduction

- The more sophisticated knee prosthesis use polycentric mechanisms with four or five axis.



- The four-bar structure gives a greater stability of the knee joint during a walking gate without active actuation of the knee than a single axis knee prosthesis.

*C.W. Radcliffe, Prosthetics and Orthotics International.*

- The most important part of bipedal robots uses a single axis knee joint.

- We purpose to use a cross-four-bar articulation for a bipedal robot and to compare the performance obtained with a single axis knee joint and with this articulation.
- We generate a set of optimal trajectories for the two types of knee articulations by parametric optimization.
- We study a planar biped.
- The trajectories are composed of single support phases and impulsive impacts.

Introduction

The Human knee joint

The Human knee joint

The knee movements

Solutions for the knee joint

Optimization and results

Conclusion

# The Human knee joint

# The Human knee joint

## Introduction

## The Human knee joint



### The Human knee joint

### The knee movements

## Solutions for the knee joint

## Optimization and results

## Conclusion



The human knee is a complex articulation with more than one degree of freedom. The knee joint allows a rolling and a sliding of the femur on the tibia in the sagittal plain. These movements are limited by the articular surfaces and the ligaments.

# The knee movements

Introduction

The Human knee joint


The Human knee joint

The knee movements


Solutions for the knee joint

Optimization and results

Conclusion



In the human case, the rolling of the femur on the tibia gives a greater flexion and prevent the erosion of the articular surfaces.





Introduction

The Human knee joint

Solutions for the knee joint

The four-bar knee

The cross four-bar solution

Study of the effect of the knee structure on the bipedal robot

Optimization and results

Conclusion

# Different solutions for the knee joint of a bipedal robot

# The four-bar knee

Introduction

The Human knee joint

Solutions for the knee joint


The four-bar knee

The cross four-bar solution

Study of the effect of the knee structure on the bipedal robot

Optimization and results

Conclusion



This structure gives a rotation and a translation on the knee joint but a singularity appears during the flexion.

Four axes knee, PROTEOR ©

*A.Hamon, Y. Aoustin, Humanoids 2009.*

# The cross four-bar solution

Introduction

The Human knee joint

Solutions for the knee joint



The four-bar knee

The cross four-bar solution

Study of the effect of the knee structure on the bipedal robot

Optimization and results

Conclusion



This structure gives a rotation and a translation on the knee joint without singularity in the flexing area.

*P. Klein and P. Sommerfeld, Biomécanique des membres inférieurs, 2008.*

# Study of the effect of the knee structure on the bipedal robot

Introduction

The Human knee joint

Solutions for the knee joint



The four-bar knee

The cross four-bar solution

Study of the effect of the knee structure on the bipedal robot

Optimization and results

Conclusion



Objective : to compare the energy consumption during the walking of a bipedal robot in function of the type of knee joint.

Introduction

The Human knee joint

Solutions for the knee joint

Optimization and results

Optimization Problem

Constraints

Problems of the cross four-bar knee

Results

Results

Conclusion

# Optimization problem and comparison of energy consumption

# Optimization Problem

Introduction

The Human knee joint

Solutions for the knee joint

Optimization and results

Optimization Problem

Constraints

Problems of the cross four-bar knee

Results

Results

Conclusion

- Objective : design a set of optimal reference trajectories for different speeds in function of the knee joints.
- Method : solving of a parametric optimization problem under constraints with a Sequential Quadratic Programming (SQP) algorithm.
- Condition : cyclic trajectories composed of single support phases and impulsive impacts.
- Criterion :

$$C_{\Gamma} = \int_0^T \sum_{j=1}^6 |\Gamma_j \dot{\Theta}_j| dt$$

## Dynamic constraints :

- no sliding of the support foot.

$$f \cdot |R_z| \leq |R_x|$$

- no rotation of the support foot.

$$ZMP_{min} \leq ZMP \leq ZMP_{max}$$

## Technologic constraints :

- $|\Gamma_j| \leq \Gamma_{max} , |\dot{\Theta}_j| \leq \dot{\Theta}_{max} , \Theta_{j_{min}} \leq \Theta_j \leq \Theta_{j_{max}} .$

- ...

# Problems of the cross four-bar knee

Introduction

The Human knee joint

Solutions for the knee joint

Optimization and results

Optimization Problem

Constraints

Problems of the cross four-bar knee

Results

Results

Conclusion

We need to consider the constraints of the closed structures in the dynamic model :


- Define the constraint equations of closed loop for each knee.
- Use the jacobian of the constraint equations with Lagrange multipliers.

$$A(X)\ddot{X} + H(X, \dot{X}) = D_{\Gamma}\Gamma + J_c^T \lambda \quad (1)$$


$\lambda$  represents the cohesion forces in the closed structures.



walking rate  $0.6 \text{ m.s}^{-1}$ ,  $h = 5\text{cm}$



Rotoide case



Cross four-bar case

Introduction

The Human knee joint

Solutions for the knee joint

Optimization and results

Optimization Problem

Constraints


Problems of the cross four-bar knee

Results


Results

Conclusion

walking rate  $0.6 \text{ m.s}^{-1}$ ,  $h = 10\text{cm}$



Rotoide case



Cross four-bar case

Introduction

The Human knee joint

Solutions for the knee joint

Optimization and results

Optimization Problem

Constraints


Problems of the cross four-bar knee

Results


Results

Conclusion

Comparison of the energy consumption ( $h = 5cm$ ):



## Comparison of the magnitude of the impact :



Introduction

The Human knee joint

Solutions for the knee  
joint

Optimization and results

Conclusion

Conclusion and  
perspectives

# Conclusion

# Conclusion and perspectives

Introduction

The Human knee joint

Solutions for the knee joint

Optimization and results

Conclusion

Conclusion and perspectives

## ■ Conclusion :

- ☐ The cross four-bar articulation reduces the energy consumption during a walking gait.
- ☐ Reduction of the impact for low walking rates.

## ■ Future works :

- ☐ Extension in 3D.
- ☐ Comparison with human movement.

Introduction

The Human knee joint

Solutions for the knee joint

Optimization and results

Conclusion

Conclusion and perspectives

Thanks for your attention!